

Bakker Magnetics Grid Magnets



- Execution : Grid magnet type RM
Sturdy construction
Permanent magnetic
- Housing: Stainless steel 1.4301
- Surface treatment : Blasted
- Magnetic part : Permanent ceramic magnets quality BM7 or Permanent Neodymium magnets quality BM35

Under normal circumstances Bakker Magnetics provides a life-time guarantee on the applied ceramic magnets.

Also available:

- Easy clean version (RM/EC)
- Automatic (cleaning) version (RM/A)
- Execution with AlNiCo magnets suitable for high temperature.

Standard Ceramic Version (RM) Square

| Article Number | Length | Width | Number of Bars | Weight (kg) |
|----------------|--------|-------|----------------|-------------|
| 25.150 | 100 | 100 | 2 | 1 |
| 25.151 | 150 | 150 | 3 | 2 |
| 25.152 | 200 | 200 | 4 | 3 |
| 25.153 | 250 | 250 | 5 | 5 |
| 25.154 | 300 | 300 | 6 | 6 |
| 25.155 | 400 | 400 | 8 | 9 |
| 25.156 | 500 | 500 | 10 | 15 |
| 25.157 | 600 | 600 | 12 | 21 |

Standard Ceramic Version (RM) Round

| Article Number | Ø dia | Number of Bars | Weight (kg) |
|----------------|-------|----------------|-------------|
| 25.100 | 100 | 3 | 0.5 |
| 25.101 | 150 | 3 | 1.5 |
| 25.102 | 200 | 4 | 3 |
| 25.103 | 250 | 5 | 4 |
| 25.104 | 300 | 6 | 5 |
| 25.105 | 350 | 7 | 7 |
| 25.106 | 400 | 8 | 8 |
| 25.107 | 450 | 9 | 10 |
| 25.108 | 500 | 10 | 13 |
| 25.109 | 550 | 11 | 16 |
| 25.110 | 600 | 12 | 20 |

Sizes and dimensions (in mm)

Contact us for more information on this product and product range Tel: **01525 372714** Email: Sales@LHS.uk.com Web: <http://www.LHS.uk.com>